EXTREME MIDRANGE

DM 6.2

Midrange 165mm or 6.5" 80W RMS, 150W MAX, 100dB Voice coil 38mm or 1.5" Magnet 30 Oz





DM 8.2

Midrange 200mm or 8" 120W RMS, 250W MAX, 100dB Voice coil 38mm or 1.5" Magnet 40 Oz



Mesh grille included for DM 6.2 and DM 8.2

DM 10.1

Midrange 250mm or 10" 200W RMS, 400W MAX, 98dB Voice cail 50mm or 2"

Voice coil 50mm or 2" Magnet 50 Oz





AN EXCLUSIVE PLUS!
SLOTS ON PHASE PLUG:
COOLING SYSTEM AND POWER ON THE DOUBLE

- ✓ high efficiency rated at 102dB (98dB on DM 10.1)
- cellulose diaphgram
- ✓ triple wave surround
- ✓ pro connectors on DM 10.1
- ✓ phase plug technology

SPECS

		DM 0.2	DM 0.2	DM IU.I
Speaker type		midrange	midrange	midrange
Diameter cone	mm (inch)	165 (6.5")	200 (8")	250 (10")
Power RMS/MAX	Watt	80/150	120/250	200/400
efficiency	dB	102	102	98
frequency respons	e Hz	300~10k	300~10k	400~5k
impedance	0hm	4	4	4
magnet weight	0z	8	15	50
voice coil	mm (inch)	38 (1.5")	38 (1.5")	50 (2")
frame material		black steel	black steel	black steel
super cooling syste	em			YES
mounting depth	mm	74	88	108



series