

DS 532.3

2-way 130mm or 5.25"
40W RMS, 80W MAX
Tweeter DTN 24
2-way HQ crossover



DS 632.3

2-way 165mm or 6.5"
50W RMS, 100W MAX
Tweeter DTN 24
2-way HQ crossover



Mesh grille included



angled



flush



surface

DTN 24

Silk Dome Tweeter
25W RMS, 50W MAX, 96dB
KVC 25mm or 1"
NeoMagnet 25x4mm
triple mounting option

49

SPECS

		DS 532.3	DS 632.3
midbass	mm (inch)	130 (5.25")	165mm (6.5")
power RMS/MAX	Watt	40/80	50/100
impedance	Ohm	4	4
frequency response	Hz	75~20k	65~20k
efficiency	dB	88	89
midbass magnet weight	Oz	8	10
mounting depth midbass	mm	54	62
tweeter model		DTN 24	DTN 24
tweeter voice coil	mm (inch)	25 (1")	25 (1")
HQ crossover w/tweeter adjustment		-3dB, 0, +3dB	-3dB, 0, +3dB



2-way HQ crossover

- ✓ carbon injection diaphragm including white/red logo
- ✓ moving phase plug
- ✓ rubber surround
- ✓ high quality dome tweeter DTN series
- ✓ pro crossover including tweeter adjustment

DS series